

Addendum #2 Hamilton East Public Library 2025 Renovation

1

Date: September 30, 2025

Project: Hamilton East Public Library – 2025 Renovation

Project #: 25022 **Pages:** 5

Bid Dates: October 9, 2025 at 2:00 pm (local time)

General Note:

The original Specifications and Drawings dated September 19, 2025 for the project referenced above are amended as noted in this Addendum No. 2. Receipt of this Addendum and any subsequent Addenda must be acknowledged on the Bid Form. Items changed or added by this addendum are to take precedence over the items or descriptions of the work in the project manual and the drawings. Items not mentioned in this addendum are to remain as described in the original plans and specifications.

Specifications Items:

Section 08 71 00 Door Hardware

1. Per the attachment, add the hardware schedule portion to the end of specification section 08 71 00.

Attachments:

1. Supplemental Specification Section 08 71 00 Door Hardware Schedule

END

138498 OPT0450036 Version 1

Legend:

Link to catalog cut sheet Felectrified Opening

Hardware Group No. 1

For use on Door #(s): 017A 017B

Provide each PR door(s) with the following:

QTY DESCRIPTION CATALOG NUMBER FINISH MFR

EA NOTE USE SALVAGE DOOR AND

HARDWARE

Hardware Group No. 2

For use on Door #(s):

102 102B 170B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 4.5 X 4.5 (NRP AS REQ)		652	IVE
1	EA	STOREROOM SET	45H 7D 14H		626	BES
1	EA	DUMMY CYLINDER	38-070 (AS REQ'D)		626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE 12/16/24/28 VAC/VDC	N	630	VON
1	EA	SURFACE CLOSER	4040XP SHCUSH		689	LCN
1	EA	ARMOR PLATE	8400 34" X 1 1/2" LDW B-CS		630	IVE
1	EA	MOP PLATE	8400 4" X 1" LDW B-CS		630	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	CREDENTIAL READER	BY ACCESS CONTROL INTEGRATOR	N		B/O
1	EA	POWER SUPPLY	PS902 120/240 VAC (COORDINATE WITH ACCESS CONTROL)	×	LGR	SCE

OPERATION: DOOR NORMALLY CLOSED AND LOCKED. PRESENTING A VALID CREDENTIAL TO THE READER WILL MOMENTARILY UNLOCK THE ELECTRIC STRIKE ALLOWING ACCESS. DOOR TO REMAIN LOCKED UPON LOSS OF POWER. FREE EGRESS AT ALL TIMES.

Hardware Group No. 3

For use on Door #(s):

168A

Provide each SGL door(s) with the following:

QTY DESCRIPTION CATALOG NUMBER FINISH MFR

EA NOTE USE SALVAGE DOOR AND

HARDWARE

Hardware Group No. 4

For use on Door #(s): 169A

Provide each SGL door(s) with the following:

		<u> </u>			
QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	CONT. HINGE	112XY	628	IVE
1	EA	PANIC HARDWARE	CD-99-NL-OP-110MD	626	VON
1	EA	SFIC MORTISE CYL.	80-102 XQ11-948	626	SCH
1	EA	SFIC RIM HOUSING	80-129	626	SCH
2	EA	PERMANENT CORE	TO MATCH OWNER'S EXISTING KEY SYSTEM		BES
1	EA	90 DEG OFFSET PULL	8190HD 18" A	630	IVE
1	EA	SURFACE CLOSER	4040XP SCUSH	689	LCN
1	EA	PA MOUNTING PLATE	4040XP-18PA AS REQ'D	689	LCN
1	EA	CUSH SHOE SUPPORT	4040XP-30 AS REQ'D	689	LCN
1	EA	BLADE STOP SPACER	4040XP-61 AS REQ'D	689	LCN
1	EA	RAIN DRIP	142AA	AA	ZER
1	EA		PERIMETER SEALS BY DOOR/FRAME SUPPLIER		B/O
1	EA	DOOR SWEEP	39A	Α	ZER
1	EA	THRESHOLD	655A	Α	ZER

Hardware Group No. 5

For use on Door #(s):

168B 169B

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
2	EA	CONT. HINGE	112XY EPT		628	IVE
2	EΑ	POWER TRANSFER	EPT10	N	689	VON
1	EA	ELEC PANIC HARDWARE	QEL-9949-EO-LBL 24 VDC	N	626	VON
1	EA	ELEC PANIC HARDWARE	QEL-9949-NL-OP-110MD-LBL 24 VDC	×	626	VON
1	EA	SFIC RIM HOUSING	80-129		626	SCH
1	EA	PERMANENT CORE	TO MATCH OWNER'S EXISTING KEY SYSTEM			BES
2	EA	90 DEG OFFSET PULL	8190HD 18" A		630	IVE
2	EA	SURFACE CLOSER	4040XP SHCUSH		689	LCN
2	EA	PA MOUNTING PLATE	4040XP-18PA AS REQ'D		689	LCN
2	EA	CUSH SHOE SUPPORT	4040XP-30 AS REQ'D		689	LCN
2	EA	BLADE STOP SPACER	4040XP-61 AS REQ'D		689	LCN
1	EA	CREDENTIAL READER	BY ACCESS CONTROL INTEGRATOR	×		B/O
1	EA	POWER SUPPLY	PS902 900-2RS (COORDINATE WITH ACCESS CONTROL)	×	LGR	SCE

OPERATION: DOOR NORMALLY CLOSED AND LOCKED. PRESENTING A VALID CREDENTIAL TO THE READER WILL MOMENTARILY RETRACT THE PANIC DEVICE LATCH ALLOWING ACCESS. CAN BE SCHEDULED TO BE UNLOCKED DURING BUSINESS HOURS. DOOR TO LOCK UPON LOSS OF POWER. FREE EGRESS AT ALL TIMES.

Hardware Group No. 6

For use on Door #(s):

168C

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	ELECTRIC STRIKE	6300 FSE 12/24 VAC/VDC	N	630	VON
1	EA	CREDENTIAL READER	BY ACCESS CONTROL INTEGRATOR	×		B/O
1	EA	POWER SUPPLY	PS902 120/240 VAC (COORDINATE WITH ACCESS CONTROL)	₩	LGR	SCE
1		NOTE	BALANCE OF EXISTING HARDWARE TO REMAIN			

OPERATION: DOOR NORMALLY CLOSED AND LOCKED. PRESENTING A VALID CREDENTIAL TO THE READER WILL MOMENTARILY UNLOCK THE ELECTRIC STRIKE ALLOWING ACCESS. DOOR TO REMAIN LOCKED UPON LOSS OF POWER. FREE EGRESS AT ALL TIMES.

Hardware Group No. 7

For use on Door #(s):

170A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	PASSAGE SET	45H 0N 14H	626	BES
1	EA	DUMMY CYLINDER	38-070 (AS REQ'D)	626	SCH
	EA	NOTE	USE SALVAGE DOOR AND		
			HARDWARE		

END OF SECTION